

circuit breaker Masterpact NW40H1 - 4000 A - 4 poles - drawout - w/o trip unit

48327

Price: 20,005,335.00 NGN

### Main

Range	MasterPacT	
Product name	MasterPact NW	
Circuit breaker name	MasterPact NW40H1	
Product or component type	Circuit breaker	
Device application	Power distribution protection	
Poles description	4P	
Neutral position	Left	
Control unit	Without control unit	
[In] rated current	4000 A at 40 °C	
Performance type	H1 65 kA 440 V AC	
[Ue] rated operational voltage	690 V AC 50/60 Hz	
Suitability for isolation	Yes conforming to EN/IEC 60947-2	
Selectivity category	Category B	
Control type	Push-button	
Mounting mode	Drawout	

### Complementary

,		
[lcu] rated ultimate short-circuit breaking capacity	65 kA at 220/415 V AC 50/60 Hz 65 kA at 440 V AC 50/60 Hz 65 kA at 525 V AC 50/60 Hz 65 kA at 690 V AC 50/60 Hz	
[Ics] rated service breaking capacity	65 kA at 220/415 V AC 50/60 Hz 65 kA at 440 V AC 50/60 Hz 65 kA at 525 V AC 50/60 Hz 65 kA at 690 V AC 50/60 Hz	
[lcw] rated short-time withstand current	65 kA 1 s 65 kA 3 s	
[lcm] rated short-circuit making capacity	143 kA 220/415 V AC at 50/60 Hz 143 kA 440 V AC at 50/60 Hz 143 kA 525 V AC at 50/60 Hz 143 kA 690 V AC at 50/60 Hz	
Sensor rating	2000 A 4000 A	
[Ui] rated insulation voltage	1000 V AC 50/60 Hz	
[Uimp] rated impulse withstand voltage	12 kV	
Power dissipation in W	900 W	

Maximum breaking time	25 ms	
Maximum closing response time	70 ms	
Mounting support	Backplate Rails	
Upside connection	Rear	
Downside connection	Rear	
Connection pitch	150 mm	
Mechanical durability	10000 cycles without maintenance 20000 cycles with maintenance	
Electrical durability	5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 AC-23A: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3	
Height	439 mm	
Width	556 mm	
Depth	395 mm	
Product weight	120 kg	
Standards	EN/IEC 60947-1 EN/IEC 60947-2	
Product certifications	CE CCC EAC	

## **Environment**

IP degree of protection	IP30 conforming to IEC 60529	
Pollution degree	4 conforming to IEC 60664-1	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	02000 m without derating 2000 m5000 m with derating	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	29.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	54.133 kg

### **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	5734
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	6a3c1e0b-44cb-4a11-80eb-a083722777c1
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No

#### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins