Product datasheet

Specifications



TeSys D contactor 3P 66A AC-3 up to 440V coil 220V AC 50/60Hz

LC1D80AM7

Main

Range	TeSys TeSys Deca	
Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
Contactor application	Motor control Resistive load	
Utilisation category	AC-1 AC-4 AC-3 AC-3e	
Poles description	3P	
[Ue] rated operational voltage	Power circuit: 690 V AC 25400 Hz Power circuit: 300 V DC	
[le] rated operational current	80 A (at <60 °C) at <= 440 V AC-1 for power circuit 66 A (at <60 °C) at <= 440 V AC-3 for power circuit 66 A (at <60 °C) at <= 440 V AC-3e for power circuit	
[Uc] control circuit voltage	220 V AC 50/60 Hz	

Complementary

22 kW at 220230 V AC 50/60 Hz (AC-3)	
37 kW at 380400 V AC 50/60 Hz (AC-3)	
37 kW at 415 V AC 50/60 Hz (AC-3)	
37 kW at 440 V AC 50/60 Hz (AC-3)	
37 kW at 500 V AC 50/60 Hz (AC-3)	
37 kW at 660690 V AC 50/60 Hz (AC-3)	
22 kW at 220230 V AC 50/60 Hz (AC-3e)	
37 kW at 380400 V AC 50/60 Hz (AC-3e)	
37 kW at 415 V AC 50/60 Hz (AC-3e)	
37 kW at 440 V AC 50/60 Hz (AC-3e)	
37 kW at 500 V AC 50/60 Hz (AC-3e)	
37 kW at 660690 V AC 50/60 Hz (AC-3e)	
5 hp at 115 V AC 60 Hz for 1 phase motors	
10 hp at 230/240 V AC 60 Hz for 1 phase motors	
20 hp at 200/208 V AC 60 Hz for 3 phases motors	
20 hp at 230/240 V AC 60 Hz for 3 phases motors	
40 hp at 460/480 V AC 60 Hz for 3 phases motors	
50 hp at 575/600 V AC 60 Hz for 3 phases motors	
LC1D	
3 NO	
With	
10 A (at 60 °C) for signalling circuit	
80 A (at 60 °C) for power circuit	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	1000 A at 440 V AC for power circuit conforming to IEC 60947	
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947	
[Icw] rated short-time withstand	640 A 40 °C - 10 s for power circuit	
current	900 A 40 °C - 1 s for power circuit	
	110 A 40 °C - 10 min for power circuit	
	260 A 40 °C - 1 min for power circuit	
	100 A - 1 s for signalling circuit	
	120 A - 500 ms for signalling circuit	
	140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1	
5	125 A gG at <= 690 V coordination type 1 for power circuit	
	125 A gG at <= 690 V coordination type 1 for power circuit	
Average impedance	1.5 mOhm - Ith 80 A 50 Hz for power circuit	
Power dissipation per pole		
i owor dissipation per pole	9.6 W AC-1	
	6.3 W AC-3	
	6.3 W AC-3e	
[Ui] rated insulation voltage	Signalling circuit: 690 V conforming to IEC 60947-1	
	Power circuit: 690 V conforming to IEC 60947-4-1	
Overvoltage category	III	
pollution degree	3	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1	
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO	
	13849-1	
Mechanical durability	6 Mcycles	
Electrical durability	0.7 Mcycles 80 A AC-1 at Ue <= 440 V	
	1 Mcycles 66 A AC-3 at Ue <= 440 V	
	1 Mcycles 66 A AC-3e at Ue <= 440 V	
Control circuit type	AC at 50/60 Hz standard	
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz	
	0.81.1 Uc (-4060 °C):operational AC 50 Hz	
	0.851.1 Uc (-4060 °C):operational AC 60 Hz	
	11.1 Uc (6070 °C):operational AC 50/60 Hz	
Inrush power in VA	140 VA 60 Hz cos phi 0.75 (at 20 °C)	
	160 VA 50 Hz cos phi 0.75 (at 20 °C)	
Hold-in power consumption in VA	13.1/4.60 Hz cos phi 0.3 (at 20 °C)	
	13 VA 60 Hz cos phi 0.3 (at 20 °C)	
	15 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	45 W at 50/60 Hz	
Operating time	419 ms opening	
	1226 ms closing	
	-	
Maximum operating rate	3600 cyc/h at 60 °C	

Connections - terminals	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end	
	Power circuit: EverLink BTR screw connectors 1 135 mm ² - cable stiffness: flexible with cable end	
	Power circuit: EverLink BTR screw connectors 2 125 mm ² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid Power circuit: EverLink BTR screw connectors 1 135 mm ² - cable stiffness: solid Power circuit: EverLink BTR screw connectors 2 125 mm ² - cable stiffness: solid Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible Power circuit: EverLink BTR screw connectors 1 135 mm ² - cable stiffness: flexible Power circuit: EverLink BTR screw connectors 1 135 mm ² - cable stiffness: flexible Power circuit: EverLink BTR screw connectors 2 125 mm ² - cable stiffness: flexible	
Tightening torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 2535 mm ² hexagonal screw head 4 mm Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 125 mm ² hexagonal screw head 4 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching voltage	17 V for signalling circuit	
Minimum switching current	5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Rail Plate	

Environment

Standards	EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 CSA C22.2 No 14 UL 60947-4-1 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ IEC 60335-1:Clause 30.2	
Product certifications	CCC CSA EAC UL KC DNV-GL LROS (Lloyds register of shipping)	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	

Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (10 Gn for 11 ms)	
Height	122 mm	
Width	55 mm	
Depth	120 mm	
Net weight	0.86 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.300 cm
Package 1 Width	13.800 cm
Package 1 Length	15.500 cm
Package 1 Weight	926.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.732 kg

Contractual warranty

Warranty

18 months

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Image: Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 38 Environmental Disclosure Product Environmental Profile

Use Better

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	
PVC free	Yes	

Use Again

\circlearrowright Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	