



Figure similar

SIMATIC S7-1200, Communication module CM 1241, RS232, 9-pole D-sub (pin), supports Freeport

General information	
Product type designation	CM 1241 RS 232
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	200 mA; From backplane bus 5 V DC
Power loss	
Power loss, typ.	1.1 W
Interfaces	
Interfaces/bus type	RS 232C (V.24)
Number of interfaces	1
Point-to-point connection	
• Cable length, max.	10 m
Integrated protocol driver	
— Freeport	Yes
— ASCII	Yes; Available as library function
— Modbus RTU master	Yes
— Modbus RTU device	Yes
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 (Standard), 2
— Parity	No parity (standard); even, uneven, mark (parity bit always 1); space (parity bit always 0)
3964 (R)	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 (Standard), 2
— Parity	No parity (standard); even, uneven, mark (parity bit always 1); space (parity bit always 0)
Modbus RTU master	
— Address area	1 through 49 999 (Standard Modbus addressing)
— max. number of devices	247; slave numbers 1 through 247, per MODBUS network segment maximum 32 devices, additional repeaters needed to expand the network to maximum configuration
protocols / Modbus RTU device / header	

— Address area		1 through 49 999 (Standard Modbus addressing)	
Interrupts/diagnostics/status information			
Diagnostics function		Yes	
Diagnostics indication LED			
• for status of the outputs		Yes	
Degree and class of protection			
IP degree of protection		IP20	
Standards, approvals, certificates			
CE mark		Yes	
CSA approval		Yes	
UL approval		Yes	
cULus		Yes	
FM approval		Yes	
RCM (formerly C-TICK)		Yes	
KC approval		Yes	
Marine approval		Yes	
Ambient conditions			
Free fall			
• Fall height, max.		0.3 m; five times, in product package	
Ambient temperature during operation			
• min.		-20 °C	
• max.		60 °C	
• horizontal installation, min.		-20 °C	
• horizontal installation, max.		60 °C	
• vertical installation, min.		-20 °C	
• vertical installation, max.		50 °C	
• permissible temperature change		5°C to 55°C, 3°C / minute	
Ambient temperature during storage/transportation			
• min.		-40 °C	
• max.		70 °C	
Air pressure acc. to IEC 60068-2-13			
• Operation, min.		795 hPa	
• Operation, max.		1 080 hPa	
• Storage/transport, min.		660 hPa	
• Storage/transport, max.		1 080 hPa	
Relative humidity			
• Operation at 25 °C without condensation, max.		95 %	
Dimensions			
Width		30 mm	
Height		100 mm	
Depth		75 mm	
Weights			
Weight, approx.		150 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564

		UNSPSC	15	32-15-17-05
Approvals / Certificates				
General Product Approval				
				
CCC	EG-Konf.		CCC	UL
General Product Approval			EMV	Test Certificates
	Miscellaneous			
VDE				Type Test Certificates/Test Report
Maritime application				other
				
ABS	BUREAU VERITAS	DNV	LRS	Confirmation
other	Environment			
Miscellaneous	Environmental Confirmations			

last modified: 7/2/2025 