

### product type designation



### CM 1243-5

communications module CM 1243-5 for connection of SIMATIC S7-1200 to PROFIBUS as DP Master module; PG/OP communication; S7 communication.

Technical Product Detail Page

<https://i.siemens.com/1P6GK7243-5DX30-0XE0>

### transfer rate

|                                                                                                |                          |
|------------------------------------------------------------------------------------------------|--------------------------|
| transfer rate                                                                                  |                          |
| <ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul> | 9.6 kbit/s ... 12 Mbit/s |

### interfaces

|                                                                                                |                            |
|------------------------------------------------------------------------------------------------|----------------------------|
| number of interfaces / according to Industrial Ethernet                                        | 0                          |
| number of electrical connections                                                               |                            |
| <ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul> | 1                          |
| <ul style="list-style-type: none"> <li>for power supply</li> </ul>                             | 1                          |
| type of electrical connection                                                                  |                            |
| <ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul> | 9-pin Sub-D socket (RS485) |
| <ul style="list-style-type: none"> <li>for power supply</li> </ul>                             | 3-pole terminal block      |

### supply voltage, current consumption, power loss

|                                                                                                            |       |
|------------------------------------------------------------------------------------------------------------|-------|
| type of voltage / of the supply voltage                                                                    | DC    |
| supply voltage / external                                                                                  | 24 V  |
| supply voltage / external / at DC / rated value                                                            | 24 V  |
| relative positive tolerance / at DC / at 24 V                                                              | 20 %  |
| relative negative tolerance / at DC / at 24 V                                                              | 20 %  |
| consumed current                                                                                           |       |
| <ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / typical</li> </ul> | 0.1 A |
| power loss [W]                                                                                             | 2.4 W |

### ambient conditions

|                                                                                                                |                |
|----------------------------------------------------------------------------------------------------------------|----------------|
| ambient temperature                                                                                            |                |
| <ul style="list-style-type: none"> <li>for vertical installation / during operation</li> </ul>                 | 0 ... 45 °C    |
| <ul style="list-style-type: none"> <li>for horizontally arranged busbars / during operation</li> </ul>         | 0 ... 55 °C    |
| <ul style="list-style-type: none"> <li>during storage</li> </ul>                                               | -40 ... +70 °C |
| <ul style="list-style-type: none"> <li>during transport</li> </ul>                                             | -40 ... +70 °C |
| relative humidity                                                                                              |                |
| <ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul> | 95 %           |
| protection class IP                                                                                            | IP20           |

### design, dimensions and weights

|                                                                           |                                     |
|---------------------------------------------------------------------------|-------------------------------------|
| module format                                                             | Compact module S7-1200 single width |
| width                                                                     | 30 mm                               |
| height                                                                    | 100 mm                              |
| depth                                                                     | 75 mm                               |
| net weight                                                                | 0.134 kg                            |
| fastening method                                                          |                                     |
| <ul style="list-style-type: none"> <li>35 mm DIN-rail mounting</li> </ul> | Yes                                 |

|                                                                                                                |                                            |
|----------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| <ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>                                       | No                                         |
| <ul style="list-style-type: none"> <li>• wall mounting</li> </ul>                                              | Yes                                        |
| <b>product features, product functions, product components / general</b>                                       |                                            |
| number of units                                                                                                |                                            |
| <ul style="list-style-type: none"> <li>• per CPU / maximum</li> </ul>                                          | 3                                          |
| <b>performance data / PROFIBUS DP</b>                                                                          |                                            |
| service / as DP master                                                                                         |                                            |
| <ul style="list-style-type: none"> <li>• DPV1</li> </ul>                                                       | Yes                                        |
| number of DP slaves                                                                                            |                                            |
| <ul style="list-style-type: none"> <li>• on DP master / operable</li> </ul>                                    | 32                                         |
| data volume                                                                                                    |                                            |
| <ul style="list-style-type: none"> <li>• of the address range of the inputs / as DP master / total</li> </ul>  | 512 byte                                   |
| <ul style="list-style-type: none"> <li>• of the address range of the outputs / as DP master / total</li> </ul> | 512 byte                                   |
| <ul style="list-style-type: none"> <li>• of the address range of the inputs / per DP slave</li> </ul>          | 244 byte                                   |
| <ul style="list-style-type: none"> <li>• of the address range of the outputs / per DP slave</li> </ul>         | 244 byte                                   |
| <ul style="list-style-type: none"> <li>• of the address range of the diagnostic data / per DP slave</li> </ul> | 240 byte                                   |
| service / as DP slave                                                                                          |                                            |
| <ul style="list-style-type: none"> <li>• DPV0</li> </ul>                                                       | No                                         |
| <ul style="list-style-type: none"> <li>• DPV1</li> </ul>                                                       | No                                         |
| <b>performance data / S7 communication</b>                                                                     |                                            |
| number of possible connections / for S7 communication                                                          |                                            |
| <ul style="list-style-type: none"> <li>• maximum</li> </ul>                                                    | 8; max. 4 connections to other S7 stations |
| <ul style="list-style-type: none"> <li>• with PG connections / maximum</li> </ul>                              | 1                                          |
| <ul style="list-style-type: none"> <li>• with PG/OP connections / maximum</li> </ul>                           | 3                                          |
| <b>performance data / multi-protocol mode</b>                                                                  |                                            |
| number of active connections / with multi-protocol mode                                                        |                                            |
| <ul style="list-style-type: none"> <li>• without DP / maximum</li> </ul>                                       | 8                                          |
| <ul style="list-style-type: none"> <li>• with DP / maximum</li> </ul>                                          | 8                                          |
| <b>performance data / telecontrol</b>                                                                          |                                            |
| protocol / is supported                                                                                        |                                            |
| <ul style="list-style-type: none"> <li>• TCP/IP</li> </ul>                                                     | No                                         |
| <b>product functions / management, configuration, engineering</b>                                              |                                            |
| configuration software                                                                                         |                                            |
| <ul style="list-style-type: none"> <li>• required</li> </ul>                                                   | STEP 7 Basic/Professional                  |
| product function / is supported / identification link                                                          | Yes; acc. to IEC 61406-1:2022              |
| <b>standards, specifications, approvals</b>                                                                    |                                            |
| reference code                                                                                                 |                                            |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>                              | KEC                                        |
| certificate of suitability / CE marking                                                                        | Yes                                        |
| certificate of suitability / UKCA marking                                                                      | Yes                                        |
| certificate of suitability / KC approval                                                                       | Yes                                        |
| certificate of suitability / Regulatory Compliance Mark (RCM)                                                  | Yes                                        |
| certificate of suitability / RoHS conformity                                                                   | Yes                                        |
| certificate of suitability / EAC approval                                                                      | Yes                                        |
| <b>standards, specifications, approvals / hazardous environments / header</b>                                  |                                            |
| certificate of suitability / ATEX                                                                              | Yes                                        |
| certificate of suitability / IECEx                                                                             | Yes                                        |
| certificate of suitability / CCC / for hazardous zone according to GB standard                                 | Yes                                        |
| certificate of suitability / FM registration                                                                   | Yes                                        |
| <b>standards, specifications, approvals / marine classification / header</b>                                   |                                            |
| Marine classification association / American Bureau of Shipping Europe Ltd. (ABS)                              | Yes                                        |
| Marine classification association / French marine classification society (BV)                                  | Yes                                        |
| Marine classification association / Det Norske Veritas (DNV)                                                   | Yes                                        |
| Marine classification association / Lloyds Register of Shipping (LRS)                                          | Yes                                        |
| Marine classification association / Nippon Kaiji Kyokai (NK)                                                   | Yes                                        |
| Marine classification association / Royal Institution of Naval Architects (RINA)                               | Yes                                        |
| <b>standards, specifications, approvals / Environmental Product Declaration</b>                                |                                            |

|                                   |          |
|-----------------------------------|----------|
| Environmental Product Declaration | Yes      |
| global warming potential [CO2 eq] |          |
| • total                           | 89.58 kg |
| • during manufacturing            | 14.29 kg |
| • during operation                | 75.11 kg |
| • after end of life               | 0.18 kg  |

#### further information / internet links

|                                                         |                                                                                                                                         |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| internet link                                           |                                                                                                                                         |
| • to website: Selection guide for cables and connectors | <a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> |
| • to web page: selection aid TIA Selection Tool         | <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>                                                         |
| • to website: Industrial communication                  | <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>                                                   |
| • to web page: SiePortal                                | <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>                                                             |
| • to website: Image database                            | <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>                                       |
| • to website: CAX-Download-Manager                      | <a href="https://siemens.com/cax">https://siemens.com/cax</a>                                                                           |
| • to website: Industry Online Support                   | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>                                                 |

#### security information

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p> |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Approvals / Certificates

##### General Product Approval



[Declaration of Conformity](#)



[China RoHS](#)

##### General Product Approval

EMV

For use in hazardous locations



[KC](#)



[FM](#)

##### For use in hazardous locations

Maritime application

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

##### Maritime application

Environment



