Specifications



# CONTACTOR 600VAC 40AMP IEC +OPTIONS

LC1D40BD

# Main

TeSys
TeSys Deca
Contactor
LC1D
Resistive load
Motor control
AC-2
AC-3
AC-1
AC-4
AC-3e
3P
Power circuit: <= 690 V AC 25400 Hz
40 A (at <60 °C) at <= 440 V AC AC-3 for power circuit
60 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
40 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
24 V DC

#### c] control circuit voltage լւ

# Complementary

Motor power kW	18.5 kW at 380400 V AC 50 Hz (AC-3)
	22 kW at 500 V AC 50 Hz (AC-3)
	30 kW at 660690 V AC 50 Hz (AC-3)
	22 kW at 1000 V AC 50 Hz (AC-3)
	22 kW at 415 V AC 50 Hz (AC-3)
	22 kW at 440 V AC 50 Hz (AC-3)
	11 kW at 220230 V AC 50 Hz (AC-3)
	9 kW at 400 V AC 50 Hz (AC-4)
	18.5 kW at 380400 V AC 50 Hz (AC-3e)
	22 kW at 500 V AC 50 Hz (AC-3e)
	30 kW at 660690 V AC 50 Hz (AC-3e)
	22 kW at 1000 V AC 50 Hz (AC-3e)
	22 kW at 415 V AC 50 Hz (AC-3e)
	22 kW at 440 V AC 50 Hz (AC-3e)
	11 kW at 220230 V AC 50 Hz (AC-3e)
Motor power hp	3 hp at 115 V AC 60 Hz for 1 phase motors
	5 hp at 230/240 V AC 60 Hz for 1 phase motors
	10 hp at 200/208 V AC 60 Hz for 3 phases motors
	10 hp at 230/240 V AC 60 Hz for 3 phases motors
	30 hp at 460/480 V AC 60 Hz for 3 phases motors
	30 hp at 575/600 V AC 60 Hz for 3 phases motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With

[Ith] conventional free air thermal current	10 A (at 60 °C) for control circuit 60 A (at 60 °C) for power circuit	
Irms rated making capacity	250 A DC for control circuit conforming to IEC 60947-5-1 800 A at 440 V for power circuit conforming to IEC 60947	
Rated breaking capacity	800 A at 440 V for power circuit conforming to IEC 60947	
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 80 A gG at <= 690 V coordination type 1 for power circuit 80 A gG at <= 690 V coordination type 2 for power circuit	
Power dissipation per pole	5.4 W AC-1 2.4 W AC-3 2.4 W AC-3e	
[Ui] rated insulation voltage	Control circuit: 600 V CSA certified Control circuit: 600 V UL certified Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Control circuit: 600 V conforming to IEC 60947-1 Power circuit: 690 V conforming to IEC 60947-1 Power circuit: 1000 V conforming to IEC 60947-4-1	
Overvoltage category	III	
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Mechanical durability	1000000 cycles	
Control circuit type	DC standard	
Coil technology	Built-in bidirectional peak limiting diode suppressor	
Control circuit voltage limits	0.10.3 Uc (-4070 °C):drop-out DC 0.751.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC	
Inrush power in W	19 W (at 20 °C)	
Hold-in power consumption in W	7.4 W at 20 °C	
Rated operational power in W	14 W at 24 V DC-13 - electrical durability: 10000000 cycles - for control circuit 48 W at 24 V DC-13 - electrical durability: 3000000 cycles - for control circuit 96 W at 24 V DC-13 - electrical durability: 1000000 cycles - for control circuit	
Operating time	20 ±20 % ms opening 50 ±15 % ms closing	
Time constant	34 ms	
Maximum operating rate	3600 cyc/h at 60 °C	
Connections - terminals	Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: rigid Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: rigid Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw terminals 1 2.525 mm <sup>2</sup> - cable stiffness: rigid Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: rigid Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.516 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.510 mm <sup>2</sup> - cable stiffness: flexible without cable end	
Tightening torque	Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver Philips No 2 Power circuit: 5 N.m - on screw terminal - with screwdriver flat Ø 6 to Ø 8 mm Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver pozidriv No 2	

Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Minimum switching voltage	17 V for control circuit	
Minimum switching current	5 mA for control circuit	
Insulation resistance	> 10 MOhm for control circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts	
Mounting support	Rail Plate	

# Environment

Standards	CSA C22.2 No 14	
	IEC 60947-4-1	
	UL 508	
	EN 60947-4-1	
	IEC 60947-5-1	
	EN 60947-5-1	
Product certifications	GL	
	BV	
	DNV	
	LROS (Lloyds register of shipping)	
	RINA	
	UL	
	CCC	
	CSA	
	GOST	
	UKCA	
	CB	
	СВ	
IP degree of protection	IP2X conforming to IEC 60529	
	IP2X conforming to VDE 0106	
Climatic withstand	conforming to IACS E10 exposure to damp heat	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Shocks contactor opened (10 Gn for 11 ms)	
	Shocks contactor closed (15 Gn for 11 ms)	
	Vibrations contactor opened (2 Gn, 5300 Hz)	
	Vibrations contactor closed (4 Gn, 5300 Hz)	
Height	127 mm	
Width	85 mm	
Depth	176 mm	
Net weight	2.185 kg	

# **Packing Units**

J	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	16.300 cm
Package 1 Length	22.000 cm
Package 1 Weight	2.256 kg
Unit Type of Package 2	S02

Number of Units in Package 2	2
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.880 kg

# **Contractual warranty**

Warranty

18 months

# Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

$\mathcal{T}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	79
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
PVC free	Yes

### Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Offer Marketing Illustration

### **Product benefits / Features**



### Offer Marketing Illustration

### **Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features** 



## **Technical Illustration**

### Assembly's dimensions

