

TeSys F contactor - 3P(3 NO)-AC-3 <= 440V 630 A with coil LX1/ LX9 - 48...1000V AC 40/400Hz, LX4 - 48...440V DC

Local distributor code: 2220927

LC1F630

① Discontinued

! Discontinued on: 11 Jan 2023

EAN Code: 3389110122183

### Main

Range	TeSys	
product name	TeSys F	
Product or component type	Contactor	
Device short name	LC1F	
Contactor application	Resistive load Motor control	
Utilisation category	AC-4 AC-1 AC-3	
Poles description	3P	
power pole contact composition	3 NO	
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC	
[le] rated operational current	1000 A (at <40 °C) at <= 440 V AC AC-1 630 A (at <55 °C) at <= 440 V AC AC-3	
Motor power kW	335 kW at 380400 V AC 50/60 Hz (AC-3) 375 kW at 415 V AC 50/60 Hz (AC-3) 400 kW at 440 V AC 50/60 Hz (AC-3) 400 kW at 500 V AC 50/60 Hz (AC-3) 450 kW at 1000 V AC 50/60 Hz (AC-3) 200 kW at 220240 V AC 50/60 Hz (AC-3) 450 kW at 660690 V AC 50/60 Hz (AC-3)	

### Complementary

[Uc] control circuit voltage	481000 V AC 40400 Hz with LX1/LX9 coil 48440 V DC with LX4 coil	
[Uimp] rated impulse withstand voltage	8 kV	
Overvoltage category	III	
[Ith] conventional free air thermal current	1000 A (at 40 °C) 1250 A	
Irms rated making capacity	6300 A AC conforming to IEC 60947-4-1	
Rated breaking capacity	5040 A conforming to IEC 60947-4-1	
[lcw] rated short-time withstand current	5050 A 40 °C - 10 s 4400 A 40 °C - 30 s 3400 A 40 °C - 1 min 2200 A 40 °C - 3 min 1600 A 40 °C - 10 min	

Associated fuse rating	630 A aM at <= 440 V 1000 A gG at <= 440 V	
Average impedance	0.12 mOhm - Ith 1000 A 50 Hz	
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C	
Power dissipation per pole	120 W AC-1 48 W AC-3	
Control circuit voltage limits	Operational: 0.851.1 Uc AC 40400 Hz with LX1/LX9 coil Drop-out: 0.250.5 Uc AC 40400 Hz with LX1/LX9 coil Operational: 0.851.1 Uc DC with LX4 coil Drop-out: 0.20.35 Uc DC with LX4 coil	
Heat dissipation	20 W	
Operating time	4080 ms closing for with LX1/LX9 coil 100200 ms opening for with LX1/LX9 coil 6070 ms closing for with LX4 coil 4050 ms opening for with LX4 coil	
Mounting support	Plate	
Standards	EN 60947-4-1 IEC 60947-4-1 IEC 60947-1 JIS C8201-4-1 EN 60947-1	
Product certifications	ABS UL RINA DNV CSA CB LROS (Lloyds register of shipping) BV RMRoS UKCA	
Connections - terminals	Power circuit: bar 2 cable(s) - busbar cross section: 60 x 5 mm  Power circuit: bolted connection  Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end  Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible with cable end  Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end  Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²solid without cable end  Control circuit: screw clamp terminals 1 cable(s) 14 mm²  Control circuit: screw clamp terminals 2 cable(s) 14 mm²	
Tightening torque	Power circuit: 58 N.m Control circuit: 1.2 N.m	
Mechanical durability	5 Mcycles	
Inrush power in VA	15001730 VA, 40400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 14201920 VA (at 20 °C)with LX4 coil	
Hold-in power consumption in VA	2025 VA, 40400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 6.512.5 VA (at 20 °C)with LX4 coil	
Maximum operating rate	1200 cyc/h 55 °C	
Compatibility code	LC1F	
Environment		
IP degree of protection	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106	
Protective treatment	тн	
ambient air temperature for operation	-555 °C	
Ambient air temperature for storage	-6080 °C	
Permissible ambient air temperature around the device	-4070 °C	

Operating altitude	3000 m without derating	
Mechanical robustness	Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 4 Gn, 5300 Hz Shocks contactor open: 6 Gn for 1/2 sine wave (11 ms) Shocks contactor closed: 15 Gn for 1/2 sine wave (11 ms)	
Height	304 mm	
Width	309 mm	
Depth	255 mm	
Net weight	18.6 kg	

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.000 cm
Package 1 Width	34.000 cm
Package 1 Length	45.000 cm
Package 1 Weight	17.110 kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	76.940 kg

## **Logistical informations**

Country of origin

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	4437
Environmental Disclosure	Product Environmental Profile

### **Use Better**

<b>⊗</b> Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins