Product datasheet

Specifications



() Discontinued

TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 150 A - coil 115 V

AC

Local distributor code: 402843056

LC1F150F7

() Discontinued on: 11 Jan 2023

EAN Code: 3389110350951

Main

Range	TeSys	
Range of product	TeSys F	
Product or component type	Contactor	
Device short name	LC1F	
Contactor application	Motor control Resistive load	
Utilisation category	AC-4 AC-1 AC-3	
Poles description	3P	
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] control circuit voltage	110 V AC 40400 Hz	
[le] rated operational current	250 A (at <40 °C) at <= 440 V AC-1 150 A (at <55 °C) at <= 440 V AC-3	

Complementary

• •		
[Uimp] rated impulse withstand voltage	8 kV 250 A (at 40 °C)	
[Ith] conventional free air thermal current		
Rated breaking capacity	1200 A conforming to IEC 60947-4-1	
[Icw] rated short-time withstand current	1200 A 40 °C - 10 s 700 A 40 °C - 30 s 600 A 40 °C - 1 min 450 A 40 °C - 3 min 350 A 40 °C - 10 min	
Associated fuse rating	160 A aM at <= 440 V 250 A gG at <= 440 V	
Average impedance	0.35 mOhm - Ith 250 A 50 Hz	
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C	
Power dissipation per pole	22 W AC-1 8 W AC-3	
Overvoltage category	III	
power pole contact composition	3 NO	

er pole contact composition 3 NC

Motor power kW	75 kW at 380400 V AC 50/60 Hz (AC-3)	
	80 kW at 415 V AC 50/60 Hz (AC-3)	
	80 kW at 440 V AC 50/60 Hz (AC-3)	
	90 kW at 500 V AC 50/60 Hz (AC-3)	
	100 kW at 660690 V AC 50/60 Hz (AC-3)	
	40 kW at 220230 V AC 50/60 Hz (AC-3)	
	22 kW at 400 V AC 50/60 Hz (AC-4)	
Control circuit voltage limits	Operational: 0.851.1 Uc 40400 Hz (at 55 °C)	
	Drop-out: 0.20.55 Uc 40400 Hz (at 55 °C)	
Mechanical durability	10 Mcycles	
Inrush power in VA	770 VA, 40400 Hz cos phi 0.9 (at 20 °C)	
Hold-in power consumption in VA	8.1 VA, 40400 Hz cos phi 0.9 (at 20 °C)	
Maximum operating rate	2400 cyc/h 55 °C	
Operating time	35 ms closing (at Uc)	
	130 ms opening (at Uc)	
Connections - terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end	
	Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end	
	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end	
	Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end	
	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid without cable end	
	Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid without cable end	
	Power circuit: bar 2 cable(s) - busbar cross section: 25 x 3 mm	
	Power circuit: lugs-ring terminals 1 cable(s) 120 mm ²	
	Power circuit: connector 1 cable(s) 120 mm ²	
	Power circuit: bolted connection	
Tightening torque	Control circuit: 1.2 N.m	
	Power circuit: 18 N.m	
Mounting support	Plate	
Heat dissipation	5.97.2 W	
Standards	IEC 60947-4-1	
	EN 60947-1	
	JIS C8201-4-1	
	IEC 60947-1	
	EN 60947-4-1	
Product certifications	LROS (Lloyds register of shipping)	
	ABS	
	BV	
	CCC	
	CB	
	RMRoS	
	DNV	
	UL	
	RINA	
	UKCA	
Compatibility code	LC1F	
Control circuit type	AC at 40400 Hz	
Environment		
IP degree of protection	IP2X front face with shrouds conforming to IEC 60529	

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106	
Protective treatment	тн	
Ambient air temperature for operation	-4060 °C	
Ambient air temperature for storage	-6080 °C	
Permissible ambient air temperature around the device	6070 °C at Uc	
Height	170 mm	
Width	163.5 mm	

Depth	171 mm	
Operating altitude	3000 m without derating	
Net weight	3.43 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.000 cm
Package 1 Width	20.000 cm
Package 1 Length	25.000 cm
Package 1 Weight	4.030 kg
Unit Type of Package 2	P06
Number of Units in Package 2	18
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	81.040 kg

Logistical informations

Country of origin

CZ

Contractual warranty

Warranty

18 months

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

${\mathcal O}$ Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 552
Environmental Disclosure Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	
SCIP Number	Fd9a8828-e2ec-48b0-8cbe-cb8a9fd887e0	
REACh Regulation	REACh Declaration	

Use Again

igodoldoldoldoldoldoldoldoldoldoldoldoldol	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins