Specifications

Main



TeSys Deca, auxiliary contact block, 2 NO, top mount, screw clamp terminals, for LC1D09 to LC1D150 contactors

LADN20

Product availability: Stock - Normally stocked in distribution facility

Range	TeSys TeSys Deca
product name	TeSys Deca
Product or Component Type	Auxiliary contact block
Device short name	LADN
Range compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D
Mounting Location	Front
Pole contact composition	2 NO
Contacts operation	Instantaneous
[Ue] rated operational voltage	690 V AC 25400 Hz
[le] rated operational current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C))
Standards	EN/IEC 60947-5-1 GB/T 14048.5 EN 50012 UL 60947-5-1 CSA C22.2 No 60947-5-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ
Product Certifications	CB Scheme UL CSA CCC EAC UKCA

Complementary

Irms rated making capacity

140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Life Is On Schneider

Permissible short-time rating	100 A 140 °F (60 °C) 1 s	
	120 A 140 °F (60 °C) 500 ms	
	140 A 140 °F (60 °C) 100 ms	
Protection type	GG fuse 10 A	
Mechanical durability	30 Mcycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Non-overlap time	1.5 ms on de-energisation no overlap between NC and NO contact	
	1.5 ms on energisation no overlap between NC and NO contact	
Insulation resistance	> 10 MOhm	
Connections - terminals	screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible with cable end	
	screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible without cable end	
	screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²)flexible with cable end	
	screw clamp terminals 2 0.0020.006 in ² (14 mm ²)flexible without cable end	
	screw clamp terminals 1 0.0020.006 in ² (14 mm ²)rigid without cable end	
	screw clamp terminals 2 0.0020.006 in ² (14 mm ²)rigid without cable end	
Tightening torque	15.05 lbf.in (1.7 N.m) flat Ø 6 mm	
3 3 1	15.05 lbf.in (1.7 N.m) Philips No 2	
	15.05 lbf.in (1.7 N.m) pozidriv No 2	
Height	1.9 in (48 mm)	
Width	1.02 in (26 mm)	
Depth	1.7 in (42 mm)	
color	Dark grey	

Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-76176 °F (-6080 °C)
Ambient air temperature for operation	23140 °F (-560 °C)
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0 12
GTIN	3389110383881
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.000 cm)
Package 1 Width	1.10 in (2.800 cm)
Package 1 Length	1.69 in (4.300 cm)
Package 1 Weight	1.199 oz (34.000 g)

Unit Type of Package 2	S03
Number of Units in Package 2	320
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	25.161 lb(US) (11.413 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	2560
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	217.156 lb(US) (98.500 kg)

Contractual warranty

Warranty

18 months

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	4
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.