

## TeSys Deca - auxiliary contact - 1 NO + 1 NO (fault)

GVAD1010

Product availability: Stock - Normally stocked in distribution facility

### Main

Range	TeSys TeSys Deca	
Device short name	GVAD	
Product or Component Type	Auxiliary contact block	
Product Compatibility	GV2L GV2P GV2RT GV3L GV2LE GV3P GV3P	
Mounting Location	Left side	
Auxiliary contacts operation	Fault signal 1 NO	
Pole contact composition	2 NO	

## Complementary

[Ui] rated insulation voltage	690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14	
[Ue] rated operational voltage	48690 V AC 24240 V DC	
[lth] conventional free air thermal current	6 A 2.5 A for fault signalling	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Protection type	GB2CB circuit breaker GG fuse 10 A	
Rated operational power in VA	300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

850 VA 380...415 V AC-15 100000 cycles 36 VA 24 V AC-14 1000 cycles 48 VA 48 V AC-14 1000 cycles 72 VA 110...127 V AC-14 1000 cycles

Rated operational power in W	120 W 240 V DC-13 100000 cycles	
	140 W 110 V DC-13 100000 cycles	
	140 W 24 V DC-13 100000 cycles	
	180 W 60 V DC-13 100000 cycles	
	240 W 48 V DC-13 100000 cycles	
	15 W 48 V DC-13 1000 cycles	
	24 W 24 V DC-13 1000 cycles	
	9 W 60 V DC-13 1000 cycles	
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals	
Height	3.5 in (89 mm)	
Width	0.4 in (9.3 mm)	
Depth	2.6 in (66 mm)	
Net Weight	0.121 lb(US) (0.055 kg)	
color	Dark grey	

## **Environment**

Environmental characteristic	Normal environment
Product Certifications	UKCA

# Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
GTIN	3389110343557	
Returnability	Yes	
Country of origin	CZ	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.59 in (1.500 cm)	
Package 1 Width	2.56 in (6.500 cm)	
Package 1 Length	3.43 in (8.700 cm)	
Package 1 Weight	1.481 oz (42.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	3.74 in (9.500 cm)	
Package 2 Width	3.94 in (10.000 cm)	
Package 2 Length	5.91 in (15.000 cm)	
Package 2 Weight	16.578 oz (470.000 g)	
Unit Type of Package 3	S02	
Number of Units in Package 3	60	
Package 3 Height	5.91 in (15.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	6.834 lb(US) (3.100 kg)	

## **Contractual warranty**

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Connections and Schema

GVAD1010



### **Technical Illustration**

### Assembly's dimensions

