Specifications



shunt trip release, SHT for EZC250, 200...240VAC

EZESHT200AC

Main

Range	EasyPact
Range of product	EZCV250 EZC250
Device short name	SHT
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	200240 V AC 50/60 Hz
Range compatibility	EasyPact EasyPact EZC

Complementary

Operating threshold	0.7 Un tripping
Auxiliary connection terminal	Lead wire

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	3.000 cm
Package 1 Length	9.000 cm
Package 1 Weight	70.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	35
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.937 kg

Contractual warranty

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins