Specifications



Circuit breaker ComPacT NSX100B, 25kA at 415VAC, TMD trip unit 63A, 4 poles 4d

C10B4TM063

Main

| Range | ComPacT |
|--|--|
| product name | ComPacT NSX |
| Device short name | NSX100B |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 4D |
| Neutral position | Left |
| [In] rated current | 63 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [lcu] rated ultimate short-circuit breaking capacity | 40 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 15 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level | B 25 kA 415 V AC |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit protection functions | L |
| control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| [Ui] rated insulation voltage | 800 V AC 50/60 Hz | |
|---|---|--|
| [Uimp] rated impulse withstand voltage | 8 kV | |
| [lcs] rated service short-circuit breaking capacity | 40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 7 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 | |
| Mechanical durability | 50000 cvcles | |

List Price displayed is VAT EXCLUSIVE.

| Electrical durability | 50000 cycles at 440 V ln/2 30000 cycles at 440 V ln 20000 cycles at 690 V ln/2 10000 cycles at 690 V ln |
|--|--|
| Power dissipation per pole | 8.61 W |
| Mounting support | Backplate |
| Mounting position | Horizontal and vertical Flat on the back |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 mm |
| Protection type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip unit rating | 63 A at 40 °C |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
| [Ir] long-time protection pick-up adjustment range | 0.71 x ln |
| Long-time protection delay adjustment type tr | Fixed |
| [tr] long-time protection delay adjustment range | 120400 s at 1.5 x ln 15 s at 6 x lr |
| Neutral protection settings | 1 x lr (4D) |
| Instantaneous protection pick-up adjustment type li | Fixed |
| [li] instantaneous protection pick- up adjustment range | 500 A |
| Earth-leakage protection | Without |
| Number of slots for electrical auxiliaries | 5 slot(s) |
| Width (W) | 140 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Product weight | 2.4 kg |

Environment

| Standards | EN/IEC 60947-2 |
|---------------------------------------|------------------------------|
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -2570 °C |
| Ambient air temperature for storage | -5085 °C |
| Relative humidity | 095 % |
| Operating altitude | 02000 m without derating |

2000 m...5000 m with derating

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.200 cm |
| Package 1 Width | 15.300 cm |
| Package 1 Length | 19.400 cm |
| Package 1 Weight | 2.315 kg |
| Unit Type of Package 2 | \$03 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 14.298 kg |

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

| Q | Environmental footprint | | |
|---|---|-------------------------------|--|
| | Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 157 | |
| | Environmental Disclosure | Product Environmental Profile | |

Use Better

| S Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 3874e08b-fcb8-4aa9-87c4-d36abebf2833 |
| REACh Regulation | REACh Declaration |
| Halogen content performance | Product contains halogen above thresholds |
| PVC free | Yes |

Use Again

| ℃ Repack and remanufacture | |
|----------------------------|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Product benefits / Features



Product benefits / Features











Wireless auxiliary contact



Long terminal shield



MN undervoltage

release



Short terminal shield

Rotary handles

MX shunt release



Standard auxiliary



contact

Standard motor mechanism module



Product benefits / Features



Product benefits / Features



Technical Illustration

Assembly's dimensions

