Specifications



Circuit breaker ComPacT NSX160B, 25kA at 415VAC, TMD trip unit 160A, 4 poles 4d

C16B4TM160

Main

Range	ComPacT	
Product name	ComPacT NSX	
Device short name	NSX160B	
Product or component type	Circuit breaker	
Device application	Distribution	
Poles description	4P	
Protected poles description	4D	
Neutral position	Left	
[In] rated current	160 A at 40 °C	
[Ue] rated operational voltage	690 V AC 50/60 Hz	
Network type	AC	
Network frequency	50/60 Hz	
Suitability for isolation	Yes conforming to EN/IEC 60947-2	
Utilisation category	Category A	
[Icu] rated ultimate short-circuit breaking capacity	40 kA lcu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA lcu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA lcu at 440 V AC 50/60 Hz conforming to IEC 60947-2 15 kA lcu at 500 V AC 50/60 Hz conforming to IEC 60947-2	
Performance level	B 25 kA 415 V AC	
Trip unit name	TM-D	
Trip unit technology	Thermal-magnetic	
Trip unit protection functions	U	
Control type	Toggle	
Circuit breaker mounting mode	Fixed	

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz	
[Uimp] rated impulse withstand voltage	8 kV	
[Ics] rated service short-circuit breaking capacity	40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 15 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2	
Mechanical durability	40000 cycles	

Electrical durability	40000 cycles at 440 V ln/2 20000 cycles at 440 V ln 15000 cycles at 690 V ln/2 7500 cycles at 690 V ln	
Power dissipation per pole	13.95 W	
Mounting support	Backplate	
Mounting position	Horizontal and vertical Flat on the back	
Upside connection	Front	
Downside connection	Front	
Connection pitch	35 mm	
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)	
Trip unit rating	160 A at 40 °C	
Long-time pick-up adjustment type Ir (thermal protection)	Adjustable	
[Ir] long-time protection pick-up adjustment range	0.71 x ln	
Long-time protection delay adjustment type tr	Fixed	
[tr] long-time protection delay adjustment range	120400 s at 1.5 x ln 15 s at 6 x lr	
Neutral protection settings	1 x lr (4D)	
Instantaneous protection pick-up adjustment type li	Fixed	
[li] instantaneous protection pick- up adjustment range	1250 A	
Earth-leakage protection	Without	
Number of slots for electrical auxiliaries	5 slot(s)	
Width (W)	140 mm	
Height (H)	161 mm	
Depth (D)	86 mm	
Net weight	2.6 kg	

Environment

Standards	EN/IEC 60947-2	
Overvoltage category	Class II	
Electrical shock protection class	Class II	
Pollution degree	3 conforming to IEC 60664-1	
IP degree of protection	IP40 conforming to IEC 60529	
IK degree of protection	IK07 conforming to IEC 62262	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-5085 °C	
Relative humidity	095 %	
Operating altitude	02000 m without derating	

2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.300 cm
Package 1 Width	14.900 cm
Package 1 Length	19.200 cm
Package 1 Weight	2.335 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	14.408 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${ \ensuremath{ \bigtriangledown \bigtriangledown}}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	246
Environmental Disclosure	Product Environmental Profile

Use Better

[⊗] Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

$^{igodoldolde{U}}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product benefits / Features



Product benefits / Features







Short terminal shield

10

ComPacT NSX



Wireless auxiliary contact



Long terminal shield



MN undervoltage

release



Rotary handles

MX shunt release





Standard auxiliary contact



Standard motor mechanism module

Product benefits / Features



Product benefits / Features



Technical Illustration

Assembly's dimensions

