Specifications



Circuit breaker, ComPacT NSX250N, 50kA/415VAC, 4 poles 4D (neutral fully protected), TMD trip unit 200A

C25N4TM200

## Main

| Wall  |   |  |
|---|---|--|
| Range   | ComPacT   |  |
| Product name  | ComPacT NSX   |  |
| Device short name                                       | NSX250N   |  |
| Product or component type                               | Circuit breaker   |  |
| Device application                                      | Distribution  |  |
| Poles description                                       | 4P  |  |
| Protected poles description                             | 4D  |  |
| Neutral position  | Left  |  |
| [In] rated current                                      | 200 A at 40 °C  |  |
| [Ue] rated operational voltage                          | 690 V AC 50/60 Hz   |  |
| Network type  | AC  |  |
| Network frequency                                       | 50/60 Hz  |  |
| Suitability for isolation                               | Yes conforming to EN/IEC 60947-2  |  |
| Utilisation category                                    | Category A  |  |
| [Icu] rated ultimate short-circuit<br>breaking capacity | 90 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>85 kA Icu at 240 V AC 50/60 Hz conforming to UL 60947-4-1<br>50 kA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1<br>15 kA Icu at 600 V AC 50/60 Hz conforming to UL 60947-4-1 |  |
| Performance level                                       | N 50 kA 415 V AC  |  |
| Trip unit name  | TM-D  |  |
| Trip unit technology                                    | Thermal-magnetic  |  |
| Trip unit protection functions                          | LI  |  |
| Control type  | Toggle  |  |
| Circuit breaker mounting mode                           | Fixed   |  |

# Complementary

| [Ui] rated insulation voltage          | 800 V AC 50/60 Hz |
|--|-------------------|
| [Uimp] rated impulse withstand voltage | 8 kV              |

| [Ics] rated service short-circuit breaking capacity          | 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 |  |
|--|--|--|
| March and a laborate little                                  | 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2   |  |
| Mechanical durability  | 20000 cycles   |  |
| Electrical durability  | 20000 cycles at 440 V ln/2<br>10000 cycles at 440 V ln<br>10000 cycles at 690 V ln/2<br>5000 cycles at 690 V ln  |  |
| Power dissipation per pole                                   | 15.4 W   |  |
| Mounting support   | Backplate  |  |
| Mounting position  | Horizontal and vertical<br>Flat on the back  |  |
| Upside connection  | Front  |  |
| Downside connection  | Front  |  |
| Connection pitch   | 35 mm  |  |
| Protection type  | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic)   |  |
| Trip unit rating   | 200 A at 40 °C   |  |
| Long-time pick-up adjustment<br>type Ir (thermal protection) | Adjustable   |  |
| [Ir] long-time protection pick-up<br>adjustment range        | 0.71 x ln  |  |
| Long-time protection delay<br>adjustment type tr             | Fixed  |  |
| [tr] long-time protection delay adjustment range             | 120400 s at 1.5 x ln<br>15 s at 6 x lr   |  |
| Neutral protection settings                                  | 1 x lr (4D)  |  |
| Instantaneous protection pick-up adjustment type li          | Adjustable   |  |
| [li] instantaneous protection pick-<br>up adjustment range   | 510 x In   |  |
| Earth-leakage protection                                     | Without  |  |
| Number of slots for electrical auxiliaries                   | 5 slot(s)  |  |
| Width (W)  | 140 mm   |  |
| Height (H)   | 161 mm   |  |
| Depth (D)  | 86 mm  |  |
| Net weight   | 2.8 kg   |  |

# Environment

| Standards                             | EN/IEC 60947-2               |
|---------------------------------------|------------------------------|
| Overvoltage category                  | III                          |
| Electrical shock protection class     | Class II front face          |
| Pollution degree                      | 3 conforming to IEC 60664-1  |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -2570 °C                     |
| Ambient air temperature for storage   | -5085 °C                     |

| Relative | humidity |
|----------|----------|
|----------|----------|

0...95 %

Operating altitude

0...2000 m without derating 2000 m...5000 m with derating

# **Packing Units**

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 14.000 cm |
| Package 1 Width              | 14.500 cm |
| Package 1 Length             | 19.000 cm |
| Package 1 Weight             | 2.662 kg  |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 3         |
| Package 2 Height             | 30.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 8 372 kg  |

Package 2 Weight

8.372 kg

# C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

| ${\mathcal Q}$ Environmental footprint |                               |
|--|-------------------------------|
| Total lifecycle Carbon footprint       | 272                           |
| Environmental Disclosure               | Product Environmental Profile |

#### **Use Better**

| Packaging made with recycled cardboard Yes   Packaging without single use plastic No   EU RoHS Directive Compliant with Exemptions   SCIP Number 3874e08b-fcb8-4aa9-87c4-d36abebf2833 | S Materials and Substances             |   |
|---|--|---|
| EU RoHS Directive Compliant with Exemptions   | Packaging made with recycled cardboard | Yes                                       |
|   | Packaging without single use plastic   | No  |
| SCIP Number 3874e08b-fcb8-4aa9-87c4-d36abebf2833  | EU RoHS Directive                      | Compliant with Exemptions                 |
|   | SCIP Number                            | 3874e08b-fcb8-4aa9-87c4-d36abebf2833      |
| REACh Regulation REACh Declaration  | REACh Regulation                       | REACh Declaration                         |
| Halogen-free status Product contains halogen above thresholds   | Halogen-free status                    | Product contains halogen above thresholds |
| PVC free Yes  | PVC free                               | Yes                                       |

#### Use Again

| $\circlearrowright$ Repack and remanufacture |                         |
|--|-------------------------|
| End of life manual availability              | End of Life Information |
| Take-back                                    | No                      |

### Offer Marketing Illustration

#### **Product benefits / Features**











Wireless auxiliary contact



Long terminal shield



MN undervoltage release

Short terminal shield



MX shunt release

Rotary handles



Standard auxiliary contact



Standard motor mechanism module

### Offer Marketing Illustration

#### **Product benefits / Features**



Offer Marketing Illustration

### Product benefits / Features



### **Technical Illustration**

### Assembly's dimensions

