

standard motor mechanism module MT400/630, ComPact NSX400/630, 220/240 VAC 50/60 Hz, 208/277 VAC 60 Hz

LV432641

### Main

| Device short name                   | MT400/630  |  |
|-------------------------------------|--|--|
| Product or component type           | Motor mechanism  |  |
| Device application                  | Automatic spring charging  |  |
| Range compatibility                 | ComPacT NSX400<br>ComPacT NSX630<br>ComPacT NSX400 DC<br>ComPacT NSX630 DC |  |
| Control type                        | Standard   |  |
| [Uc] control circuit voltage        | 208277 V AC 60 Hz<br>220240 V AC 50/60 Hz                                  |  |
| circuit breaker mounting mode       | Fixed  |  |
| circuit breaker frame rated current | 400 A<br>630 A   |  |

# Complementary

| Control signal type             | Impulse<br>Maintained                                 |
|---------------------------------|---|
| circuit breaker response time   | < 700 ms open<br>< 80 ms closed                       |
| Maximum operating frequency     | 4 per minute  |
| Maximum power consumption in VA | 500 VA closing<br>500 VA opening                      |
| Locking options description     | Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8 |

### **Packing Units**

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 19.800 cm |
| Package 1 Width              | 17.500 cm |
| Package 1 Length             | 17.500 cm |
| Package 1 Weight             | 3.104 kg  |
| Unit Type of Package 2       | S04       |
| Number of Units in Package 2 | 6         |
| Package 2 Height             | 30.000 cm |
| Package 2 Width              | 40.000 cm |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Package 2 Length             | 60.000 cm  |
|------------------------------|------------|
| Package 2 Weight             | 19.326 kg  |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 24         |
| Package 3 Height             | 50.000 cm  |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 88.506 kg  |

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint        |                               |
|----------------------------------|-------------------------------|
| Total lifecycle Carbon footprint | 26                            |
| Environmental Disclosure         | Product Environmental Profile |

### **Use Better**

| Packaging made with recycled cardboard | No  |
|--|---|
| Packaging without single use plastic   | No  |
| EU RoHS Directive                      | Compliant with Exemptions                 |
| SCIP Number                            | 768b9546-0496-496b-9dda-45dc807dcf86      |
| REACh Regulation                       | REACh Declaration                         |
| Halogen-free status                    | Product contains halogen above thresholds |

### **Use Again**

| ○ Repack and remanufacture      |   |
|---------------------------------|---|
| End of life manual availability | End of Life Information   |
| Take-back                       | No  |
| WEEE Label                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |