

Product datasheet

Specifications



C60 - circuit breaker - C60N - 2P - 6A - B curve

24075

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range of product	C60
Range	Multi9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	2P
Number of protected poles	2
Neutral position	Left
[In] rated current	6 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	10 kA Icu at 400...415 V CA 50/60 Hz conforming to EN/IEC 60947-2 6 kA Icu at 440 V CA 50/60 Hz conforming to EN/IEC 60947-2 6000 A Icn at 230/400 V CA 50/60 Hz conforming to EN 60898 20 kA Icu at 125 V CC 2P conforming to EN/IEC 60947-2 20 kA Icu at 230...240 V CA 50/60 Hz conforming to EN/IEC 60947-2 30 kA Icu at 125 V CC 3P conforming to EN/IEC 60947-2 40 kA Icu at <= 250 V CC 4P conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	440 V CA 50/60 Hz 230...240 V CA 50/60 Hz 400...415 V CA 50/60 Hz <= 250 V CC 230/400 V CA 50/60 Hz
Magnetic tripping limit	3...5 x In
[Ics] rated service breaking capacity	7.5 kA conforming to EN/IEC 60947-2 - 230...240 V CA 50/60 Hz 2.25 kA conforming to EN/IEC 60947-2 - 440 V CA 50/60 Hz 3.75 kA conforming to EN/IEC 60947-2 - 400...415 V CA 50/60 Hz 6000 A conforming to EN 60898 - 230/400 V CA 50/60 Hz
Limitation class	3 conforming to IEC 60898
Contact position indicator	Yes
Control type	Toggle

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	73 mm
Net weight	0.24 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals16 mm² flexible Tunnel type terminals25 mm² rigid
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60947-2 IEC 60898
Overvoltage category	IV
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	7.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	210 g

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
EU RoHS Directive	Compliant with Exemptions
Halogen-free status	Halogen free product