

Product datasheet

Specifications



Circuit breaker frame, MasterPact NW40H1, 4000A, 65kA/440VAC 50/60Hz (Icu), 4 poles, fixed, without control unit

48097

Main

Range	MasterPacT
Product name	MasterPact NW
Circuit breaker name	MasterPact NW40H1
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	4P
Neutral position	Left
Control unit	Without control unit
[In] rated current	4000 A at 40 °C
Performance type	H1 65 kA 440 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Fixed

Complementary

[Icu] rated ultimate short-circuit breaking capacity	65 kA at 220/415 V AC 50/60 Hz 65 kA at 440 V AC 50/60 Hz 65 kA at 525 V AC 50/60 Hz 65 kA at 690 V AC 50/60 Hz
[Ics] rated service breaking capacity	65 kA at 220/415 V AC 50/60 Hz 65 kA at 440 V AC 50/60 Hz 65 kA at 525 V AC 50/60 Hz 65 kA at 690 V AC 50/60 Hz
[Icw] rated short-time withstand current	65 kA 1 s 65 kA 3 s
[Icm] rated short-circuit making capacity	143 kA 220/415 V AC at 50/60 Hz 143 kA 440 V AC at 50/60 Hz 143 kA 525 V AC at 50/60 Hz 143 kA 690 V AC at 50/60 Hz
Sensor rating	2000 A 4000 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	650 W

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum breaking time	25 ms
Maximum closing response time	70 ms
Mounting support	Backplate Rails
Upside connection	Rear
Downside connection	Rear
Connection pitch	150 mm
Mechanical durability	10000 cycles without maintenance 20000 cycles with maintenance
Electrical durability	5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 AC-23A: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3
Height	352 mm
Width	537 mm
Depth	297 mm
Net weight	65 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Product certifications	CE CCC EAC

Environment

IP degree of protection	IP30 conforming to IEC 60529
Pollution degree	4 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.500 cm
Package 1 Width	29.500 cm
Package 1 Length	49.500 cm
Package 1 Weight	47.251 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	3998
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	6a3c1e0b-44cb-4a11-80eb-a083722777c1
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins